

GateStar 1000

Commercial Duty Slide Gate Operator



Product No. See table below



Commercial duty slide gate operator series, available in 1/2 horsepower, 115V or 230V supply voltage, 12" or 24" per second gate speed.

RATINGS

- Maximum duty cycle: Continuous
- Shipping weight: 185 lbs.

FEATURES

- Welded Uni-body frame
- Architecturally designed, long-life cover
- Heavy, key-locked steel cover
- High efficiency, non-slip belt drive
- 1/2 H.P. instant-reverse, 3-wire motor
- DC solenoid actuated lock mechanism
- Overload sensing system
- Built-in auto-close timer
- Timer re-close on/off switch
- MVP "smart" radio receiver with FC antenna
- Built-in "smart" self-adjusting maximum run timer
- Built-in master/second capability
- Audio alarm and Safe Secure™ open/close push button enabled on alarm only
- Standard speed UL Listed for UL 325 (Class I-IV) for U.S. and Canada
- High speed UL Listed for UL 325 (Class IV) for U.S. and Canada

MODEL	HP	VOLTAGE & PHASE	GATE SPEED	MAXIMUM GATE WEIGHT	MAXIMUM GATE LENGTH
GSX1000 5011	1/2	115V 1P	12"/sec	1575 lbs.	45 ft.
GSX1000 5011-HS			24"/sec	800 lbs.	25 ft.
GSX1000 5021	1/2	230V 1P	12"/sec	1575 lbs.	45 ft.
GSX1000 5021-HS			24"/sec	800 lbs.	25 ft.

ELECTRICAL

- Solid-state circuitry and motor control with diagnostic LED readout
- Electronic dynamic braking
- Built-in free exit and reversing loop detector sockets

MECHANICAL

- #40 chain on standard speed (25 ft. included)
- #50 chain on high speed (25 ft. included)

FACTORY OPTIONS

- Fail safe lock (gate unlocked when power off)
- # 50 chain (standard on HS high speed models)

WARRANTY

- 5 years